

PA	PART NO. P2RFC-2068-XX						
RE	DESCRIPTION	DWN	DATE	APPROVED			
Г	ENGINEERING RELEASE	CZS	09/27/16	JDMc			





SPECIFICATIONS:

IMPEDANCE: 50 Ohms

FREQUENCY RANGE: 0-6 GHz

3RD ORDER IM: ≤-155 dBc @ 700MHz & 1900MHz 3RD ORDER IM TEST METHOD: 2x43dBm CARRIERS

VSWR: ≤1.15:1 THRU 3GHz

NOTE: BOTH CONNECTORS WILL HAVE PROTECTIVE CAPS ON

4	TFT-402-LF	1	PLENUM CABLE		Þ
3	TUBING	2	HEAT SHRINK		Ļ
2	RSA-3500-SR2LP	1	SMA MALE CONNECTOR	WHITE BRONZE	ľ
1	RFN-1002-SR2FL	1	N MALE CONNECTOR	WHITE BRONZE	ե
#	PART NUMBER	QTY	DESCRIPTION	FINISH	

CUSTOMER OUTLINE DRAWING

ALL DIMENSIONS ARE REFERENCE ONLY

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES AND [MILLIMETERS]

DRAWN 09/27/16 C. ZUNIGA CHECKED ORJ DRAWN 09/27/16 C. ZUNIGA

PROPRIETARY AND CONFIDENTIAL

THIS DRAWING CONTAINS
INFORMATION PROPRIETARY TO
RF INDUSTRIES, ANY
UNAUTHORIZED USE OF THIS
DRAWING IS EXPRESSLY
PROHIBITED WITHOUT WRITTEN PERMISSION FROM RF
INDUSTRIES. ANY VIOLATION IS
PUNISHABLE UNDER U.S. COPYRIGHT LAWS.



7610 MIRAMAR RD. SAN DIEGO, CA 92126

N MALE TO SMA MALE

CABLE ASSEMBLY

13	SIZE	CABLE	GROUP	P2RFC-2068-XX				REV	
	SCALE	: NTS	ENGINEE	RING I	000000 SHEET	1	OF	1	