





STANDARD CABLE LENGTHS ["L"]: CABLE LENGTHS ["L"]: -12 [1 FOOT] -24 [2 FEET] -144 [12 FOOT] -36 [3 FEET] -180 [15 FEET] -48 [4 FEET] -216 [18 FEET] -60 [5 FEET] -300 [25 FEET -72 [6 FEET] -600 [50 FEET] -900 [75 FEET] -1200 [100 FEET]

| CUST    | CUSTOMER |  |  |  |  |
|---------|----------|--|--|--|--|
| OUTLINE | DRAWING  |  |  |  |  |

C. ZUNIGA

C. ZUNIGA

CHECKED

ALL DIMENSIONS ARE REFERENCE ONLY

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES AND [MILLIMETERS]

09/22/15

09/22/15

## 3 LMR-400 1 CABLE 2 ST-P0250A-K 2 TUBING HEAT SHRINK 2 N PLUG CRIMP 1 RFN-1006-3I SILVER ORJ DRAWN DESCRIPTION PART NUMBER QTY FINISH

## PROPRIETARY AND CONFIDENTIAL

THIS DRAWING CONTAINS
INFORMATION PROPRIETARY TO
RF INDUSTRIES, ANY
UNAUTHORIZED USE OF THIS DRAWING IS EXPRESSLY PROHIBITED WITHOUT WRITTEN PERMISSION FROM RF INDUSTRIES. ANY VIOLATION PUNISHABLE UNDER U.S. COPYRIGHT LAWS.



7610 MIRAMAR RD.

-1800 [150 FEET]

## N PLUG CRIMP TO N PLUG CRIMP

| ZI | SIZE  | CABLE    | GROUP   | RFW-5580-XX |              |       |   | REV |   |
|----|-------|----------|---------|-------------|--------------|-------|---|-----|---|
|    | SCALE | :<br>NTS | ENGINEE | RING ID     | D:<br>000000 | SHEET | 1 | OF  | 1 |