

NEW PRODUCT RELEASEImproved Environmental Performance for Solderless N Connector



includes a "weep hole" for optional solder installation.

The majority of N type connectors are installed at remote sites exposed to the environment. The RF Connectors Division of RF Industries offers an improved N male connector for high performance .400 inch diameter cables. Part number RFN-1006-I-WB features white bronze plating for a non-tarnish finish with enhanced electrical performance. The plating is ferrous metal free, which reduces inter-modulation interference. A ridged back end provides better sealing for the heat shrink boot included with the connector. A combination hex/knurl coupling nut allows for wrench or finger mating. The connector may be attached to multiple brands of high performance cables including Times LMR®-400, Andrew CNT®-400, CommScope WBC®-400 and Belden® RF-400. The connector is assembled with industry standard crimp tools with .429 inch and .118 inch hex dies. The contact design

Available from RF Connectors Distributors throughout the world. For additional information call 800-233-1728 or 859-549-6340. You can also e-mail: RFI@rfindustries.com. Visit our web site at www.rfindustries.com.

RF Connectors is a division of RF Industries (NASDAQ RFIL) a leading supplier of connecting solutions provided through its operation divisions: RF Connectors, RF Cable Assembly, Aviel Electronics, RF Neulink, RadioMobile and Worswick/OddCables.

All trademarks are the property of their respective owners.