NOTES:	UNLESS	OTHERWISE SPECIFIED					REV	ECR DES	SCRIPTION	l	BY	DATE	CHECKED	
		MATERIALS AND COMPONENTS ARE ROHS/REACH COMPLIANT. CONNECTORS MEET THE REQUIREMENTS OF ANSI/TIA 568-C.3						A	- INIT	IAL RELEA	ASE	K.T.	04/01/2019	M.K.
		TESTED FOR OPTICAL PERFORMANCE, END FACE CRITERIA	AND CLEAN	LINESS.								1	0 1/0 1/2010	
		E ASSEMBLIES ARE MANUFACTURED TO C ENTERPRISES ST	TANDARDS.											
	5. STAN	IDARDS AND SPECIFICATIONS AVAILABLE UPON REQUEST.												
	ASSEMBLY LENGTH													
	-					\							-	
													VIEV	V A
	Q													
					VIEW A									
					SS SECTION TO SCALE									
		Ø 3.	0 mm ——											
						900 u	m TIGHT-BU	FFERED FIBER						
						A	RAMID YARN	l						
					$\mathcal{I}_{\mathcal{I}}$		JTER JACKE	:т						
						0.	OTEN SHORE	. 1						
							DESCRIPTI	ION: SC-NOCI	LIP UPC POLIS	SH / UNTER	RMINATED OS2 3.0 mm	SIMPLEX	OFNR CABL	E, SUPRA
							DRAWN BY:	K. THOMAS	04/01/2019				ENTERPR	
							APVD					V	445 CADES ISTA CA 92	2081
		BILL OF MATERIALS					BY:	M. KHANFIR	04/01/2019	Conn	ENTERPRISES ecting Today's Infrastructures	7	60-599-511	1
ITEM	QTY	COMPONENT	UPC TEST LIMITS AT 1310 nm			DIMENSIONS: METRIC [IMPERIAL]				TITLE: SC/UNTERM OS2 3.0 mm SIM				
2	AR	SINGLE-MODE OS2 SIMPLEX OFNR 3.0 mm CABLE, YELLOW: CORNING	MAX.	TYP.	MIN.	TYP.	PROPRIETARY AND CONFIDENTIAL						/	REV A
4		SC-UNCLIPPED UPC POLISH CONNECTOR; BLUE	I.L.	I.L.	R.L.	R.L.	INFORMATION	N OF C ENTERPRIS	ITAINS PROPRIETARY NTERPRISES. NOT TO BE SCLOSED WITHOUT					A
1	1	HOUSING, BLUE BOOT: PERFORMA	≤0.50dB	0.20dB	3 ≥50dB	60dB		RMISSION. ALL RIG		1	SCALE: NOT TO SCALE		SHEET	4054