NOTES: UNLESS OTHERWISE SPECIFIED DESCRIPTION DATE CHECKED REV ECR BY 1. MATERIALS AND COMPONENTS ARE RoHS/REACH COMPLIANT. Α INITIAL RELEASE K.T. 06/10/2016 A.J. 2. CONNECTORS MEET THE REQUIREMENTS OF ANSI/TIA 568-C.3 3. 100% TESTED FOR OPTICAL PERFORMANCE, END FACE CRITERIA AND CLEANLINESS. 4. CABLE ASSEMBLIES ARE MANUFACTURED TO C ENTERPRISES STANDARDS. 5. STANDARDS AND SPECIFICATIONS AVAILABLE UPON REQUEST. 6 HEAT SHRINK. LENGTH [24 IN] 900 um TIGHT-BUFFERED FIBER -VIEW A Ø 6.3 mm -6\ VIEW A CROSS SECTION 11 NOT TO SCALE 12 900 um TIGHT-BUFFERED FIBER DIELECTRIC STRENGH MEMBERS FOAM PACKING BLOCK DIELECTRIC STRENGH MEMBERS DIELECTRIC STRENGH MEMBERS -**OUTER JACKET** 4 FLAME RETARDENT FIBERS AND CONNECTORS DRAWN **C ENTERPRISES** K. THOMAS 06/10/2016 SECURED IN A FOAM BLOCK BY: 2445 CADES WAY AND BAGGED. VISTA CA 92081 APVD A. JENSEN 06/10/2016 **C**·ENTERPRISES 760-599-5111 BY: TITLE: SURI12LBXX9XXUX DIMENSIONS: METRIC [IMPERIAL] **BILL OF MATERIALS** DWG. NO. REV SIZE PRODUCT ITEM QTY PROPRIETARY AND CONFIDENTIAL SURI12LBXX9XXUX Α SINGLE-MODE OS2 OFNR DIST CABLE; YELLOW: CORNING THIS DOCUMENT CONTAINS PROPRIETARY 2 AR INFORMATION OF C ENTERPRISES. NOT TO BE USED, COPIED, OR DISCLOSED WITHOUT LC-UNCLIPPED UPC POLISH; BLUE HOUSING, BLUE BOOT: SCALE: NOT TO SCALE SHEET 1 OF 1 1 12 WRITTEN PERMISSION. ALL RIGHTS RESERVED. CORNING