

NOTES: UNLESS OTHERWISE SPECIFIED


1. MATERIALS AND COMPONENTS ARE RoHS/REACH COMPLIANT.
2. CONNECTORS MEET THE REQUIREMENTS OF ANSI/TIA 568-C.3
3. 100% TESTED FOR OPTICAL PERFORMANCE, END FACE CRITERIA, AND CLEANLINESS.
4. 2.0 mm DIAMETER TYPICAL. 900 um, 1.6 mm and 3 mm AVAILABLE.
5. POLISH TYPES: PC, UPC, APC
6. TESTED TO 850 nm (MULTIMODE) OR TO 1550 nm (SINGLE-MODE) UPON REQUEST.
7. ALTERNATE COLOR JACKETS LISTED IN C ENTERPRISES STANDARDS.
8. CABLE ASSEMBLIES ARE MANUFACTURED TO C ENTERPRISES STANDARDS.
9. STANDARDS AND SPECIFICATIONS AVAILABLE UPON REQUEST.

REV	ECR	DESCRIPTION	BY	DATE	CHECKED
A	-	INITIAL RELEASE	J.V.	03/23/2015	-
B	-	DRAWING FORMAT UPDATE. BLOCKS UPDATE.	K.T.	03/11/2016	A.J.
B.1	-	TEST PERFORMANCE TABLE.	K.T.	11/15/2016	A.J.

LENGTH



TEST PERFORMANCE						
TYPE	TEST FREQ.	FINISH	MAX. I.L.	TYP. I.L.	MIN. R.L.	TYP. R.L.
MULTIMODE	1300 nm	PC	<=0.75dB	0.20dB	N/A	25dB
SINGLE-MODE	1310 nm	UPC	<=0.50dB	0.20dB	>=50dB	60dB
SINGLE-MODE	1310 nm	APC	<=0.50dB	0.20dB	>=65dB	68dB

DRAWN BY:	K. THOMAS	02/05/2016	 <p>C ENTERPRISES 2445 CADES WAY VISTA CA 92081 760-599-5111</p>
APVD BY:	A. JENSEN	03/11/2016	
DIMENSIONS: METRIC [IMPERIAL]			TITLE: FIBER SIMPLEX AFOP
PROPRIETARY AND CONFIDENTIAL			SIZE DWG. NO. REV
THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION OF C ENTERPRISES. NOT TO BE USED, COPIED, OR DISCLOSED WITHOUT WRITTEN PERMISSION. ALL RIGHTS RESERVED.			A FIBER-SIMPLEX-AFOP B.1
SCALE: NOT TO SCALE			SHEET 1 OF 1