



# RF Attenuators

## 5 Watt N Male to N Female

### Features

Wide Frequency Band DC-3GHz

2G/3G/4G/5G/LTE Coverage

Low VSWR

Widely used for In-building Solutions

In-line, bi-directional attenuators for managing signal power levels. Available in various attenuation values, connectors, frequencies and power levels. Applications include Distributed Antenna Systems (DAS), test equipment and electrical circuits where power levels need to be reduced.



### GENERAL SPECIFICATIONS

Frequency Range .....	DC-3GHz
Impedance.....	50Ω
Power Rating .....	5 (average)
VSWR .....	≤1.20
Applications.....	Indoor
Temperature Range.....	-30° C to +65° C
Connector Type .....	N male to N female
Housing Material.....	Aluminum
Color.....	Silver
Weight.....	0.15 (kg)

Model Number	Attenuation (dB)	Accuracy (dB)
RF-ATN-NMF-5W3	3dB	±0.8
RF-ATN-NMF-5W6	6dB	±0.8
RF-ATN-NMF-5W10	10dB	±1.0
RF-ATN-NMF-5W20	20dB	±1.5

### RF Industries

(NASDAQ: RFI)

16868 Via Del Campo Court  
Suite 200  
San Diego, CA 92126

(800) 233-1728  
(858) 549-6340  
Fax: (858) 549-6345

rfi@rfindustries.com  
www.rfindustries.com

