




PROFESSIONAL GRADE COAXIAL DIES		
Photograph	Description	Part Number
	Hex cavity: .610"	RFA-4009-01
	Hex cavities: .042", .068", .255"	RFA-4009-03
	Hex cavities: .068", .130", .178"	RFA-4009-04
	Hex cavities: .100", .118", .429"	RFA-4009-05
	Hex cavities: .068", .100", .213"	RFA-4009-06

COMMERCIAL GRADE MODULAR DIES		
Photograph	Description	Part Number
	For non-insulated terminals AWG 22-8	RFA-4005-21
	For non-insulated flag terminals from 0.5 to 2.5 sq.mm. AWG 22-18, 16-14	RFA-4005-22
	For cord end terminals from 0.5 to 10 sq.mm. AWG 22-8	RFA-4005-23
	For insulated terminals from 0.5 to 6 sq.mm. AWG 22-18, 16-14, 12-10	RFA-4005-24
	For non-insulated open barrel terminal from 0.5 to 6 sq.mm. AWG 22-18, 16-14, 12-10	RFA-4005-25
	For non-insulated terminals and cable lugs from 1.5 to 6 sq.mm. AWG 22-18, 16-14, 12-10	RFA-4005-26
	For non-insulated terminals DIN 46234 from 0.5 to 10 sq.mm. AWG 22-18, 16-14, 12-10, & 8	RFA-4005-27

COMMERCIAL GRADE COAXIAL DIES		
	RG-58/U, RG-59/U, RG-142/U, RG-223/U, RG-400/U, RG-8X, Proflex and various video cables, cavity dimensions: .052", .068", .100", .213" and .255"	RFA-4005-01
	RG-8/U, RG-213/U, RG-214/U, and Belden 9913 cables, cavity dimensions: .100", .128" & .429". The .128" cavity crimps the center pin on Belden 9913 cable.	RFA-4005-02
	.228", .068", .305", for RG-58/U, RG-59/U, RG-62/U and Cambridge connectors series CP-88 & CP-89	RFA-4005-04
	.155", .184", .215"	RFA-4005-05
	.255", .324", .360" for RG-59/U, RG-6/U, and F-Type (CATV) coax connectors	RFA-4005-06
	.213", .178", .068", .042", for RG-58/U, RG-174/U, RG-316/U coax connectors (RFI cable groups B and C)	RFA-4005-07
	.324", .255", .068", .042", for RG-59/U and Belden 8281 coax cable (RFI cable groups D and G)	RFA-4005-08
	.178", .130", .068", for RG-174/U, RG-188/U, RG-316/U and mini 59/U coax connectors (RFI cable group B)	RFA-4005-09
	.080", .100", .429" for RG-8/U, RG-11/U and RG-213/U (RFI cable group E)	RFA-4005-10
	Belden 9913, LMR@-400, WBC-400 (RFI cable group I); .429", .118" hex cavities	RFA-4005-14



All dies are available separately