



Cross Reference to:
CNT®-240 and
RG-8X cable

Loss comparable to
semi-rigid cable

50 dB better than
single shielded
cable

Available
pre-terminated

RoHS Compliant



RF Industries

(NASDAQ: RFI)

16868 Via Del Campo Court
Suite 200

San Diego, CA 92127

(800) 233-1728

(858) 549-6340

Fax: (858) 549-6345

rfi@rfindustries.com

www.rfindustries.com

ELECTRICAL CHARACTERISTICS

Maximum Frequency 8000 MHz

Characteristic Impedance 50 ±3 ohm

Capacitance 23.8 pF/ft

Velocity of Propagation >83%

DC Resistance

Inner Conductor <3.35 ohms/1000 ft

Outer Conductor <3.65 ohms/1000 ft

Jacket Spark 5000 Volts RMS

Voltage Withstanding 1000 Volts DC

Return Loss

5-1000 MHz 23 dB

1000-3000 MHz 21 dB

Insulation Resistance >100,000 MΩ-km

Shielding Effectiveness

100-3000 MHz >90 dB

MECHANICAL PROPERTIES

Minimum Bending Radius

Installation 0.75"

Repeated 2.5"


Maximum Pulling Tension 80 lbs

Flat Plate Crush 20 lbs

Rated Temperature

Storage/Operating -40 / +85°

Outdoor Installation -40 / +85°



CONSTRUCTION

Inner Conductor BC

Conductor Diameter 0.056"

Dielectric Foam PE

Insulation Diameter 0.150"

Color Neutral

Shielding Aluminum Tape (bonded)

Thickness AL/PET-Foil 10/15 μm

Outer Conductor TC Wire Braid

Conductor Diameter 0.0047"

No. of Wires 144

Coverage (±3%) 92

Jacket PE

Outer Diameter 0.240"

Color Black

UV Outdoor Rated Compliant

ATTENUATION AND AVERAGE POWER

Frequency, MHz	Attenuation, dB/100ft	Attenuation, dB/100m
30	1.34	4.40
50	1.70	5.58
150	3.01	9.90
220	3.70	12.14
450	5.29	17.38
900	7.60	24.93
1500	9.90	32.50
1800	10.92	35.83
2000	11.50	37.73
2500	12.92	42.40
5800	20.42	67.00
8000	24.29	79.70

ROHS GUIDELINES

Cadmium (Cd).....	<0.01%	Chromium (VI)	<0.1%
Lead (Pb)	<0.1%	Polybrominated Biphenyls (PBB)	<0.1%
Mercury (Hg)	<0.1%	Polybrominated Diphenyl Ether (PBDE) ..	<0.1%

Note: Specifications subject to change without notice

CBL-CU240 is a registered trademark of RF Industries. CNT is a registered trademark of CommScope.

Revision 4 | July 2025