

Comp Pro® Compression Connectors

for LMR®-400 and Equivalent Braided Cables

COMP-TM-400

Compression Connector

Cable Types: LMR®-400, RG-8/U, WBC400,

AA-6146, CBL-CU400 & Eupen 213RTS

Components

<u> </u>	
Interface Type	TNC, Male
Body & Hex Coupling Nut	White Bronze (tri-metal)
Inner Contact	Gold Plated Brass
Internal Post	Tin Plated Brass
Compression Ring	Brass
Clamp	UHMWPE
Insulator	Ultem® 1000
Gasket	Silicone Rubber

COMPRESSION LENGTH FINGER GRIPS CABLE MARKING GUIDE - 1.94" -

Environmental

Moisture Resistance Test	MIL-STD-202F, Method 106F
Mechanical Shock Test	MIL-STD-202F, Method 213B, Test Condition C
Corrosion Test	MIL-STD-1344A, Method 1001.1, Test Condition A
Thermal Shock Test	MIL-STD-202F, Method 107G, Test Condition A-1, Low Temp -55°C
Vibration Test	IEC 68, PART 2-6
Operating Temp. Range	-67°F to +185°F / -55°C to +85°C
Storage Temperature	-67°F to +185°F / -55°C to +85°C
Immersion Test	IEC 529:1989, IP68
Immersion Depth	12" 0.31 m
Water Jetting Test	IEC 529:1989, IP66

Mechanical

Inner Attachment Method	360° Collet
Outer Attachment Method	Compression
Connector Weight	1.565 oz. 44.4 g
Minimum Connector Retention Tensile Force	890 N 200 lbs.
Minimum Coupling Nut Torque	14 in-lbs. 1.6 N-m
Hex Width	0.55" 14 mm

Electrical Characteristics

Maximum Operating Frequency	6 GHz
Connector Impedance	50 Ω
Return Loss	-35 dB, 0-1 GHz -32 dB, 1-3 GHz
Insertion Loss	.10 √freq (GHz)

Tools		
Complete Tool Kit	KIT400NT	
KIT400 includes the following tools, replacements may also be ordered		
Compression Tool	VT500	
Cable Cutter	CXC	
Prep Tool, Cartridge Trimmer	SDT400-50	
Replacement Blades	RC400-50	
Insertion Tool for N Connector	IT50NM	
Adapter, Insertion Tool for TNC	IT50TA	
Torque Wrench for N Connector	TW1412	
Torque Wrench for TNC Connector	TW08X14MM	
Marking Guide	MCAP400	
Marking Pen	PEN-50	
Tool Bag	POUCH-50	
optional Tools		
Torque Wrench for 7-16 DIN Connector	TQ-114-F18 (optional)	

RFA-4420

(optional)

Prep Tool/Cable Devil™