


PART NO.		P2RFC-2312-XX		
REV	DESCRIPTION	DWN	DATE	APPROVED
—	ENGINEERING RELEASE	CZS	05/20/20	JDMc



P2RFC-2312-XX
 [\"L\"] LENGTH IN INCHES
 CONFIGURATION ID
 CABLE ASSEMBLY DESIGNATOR

STANDARD CABLE LENGTHS [\"L\"]:

- 12 [1 FOOT]
- 24 [2 FEET]
- 36 [3 FEET]
- 48 [4 FEET]
- 60 [5 FEET]
- 72 [6 FEET]

FOR CUSTOM LENGTHS REPLACE XX
FOR NUMBER OF INCHES

SPECIFICATIONS:

IMPEDANCE: 50 Ohms
 FREQUENCY RANGE: 0–6 GHz
 3RD ORDER IM: ≤ -155 dBc @ 700MHz & 1900MHz
 3RD ORDER IM TEST METHOD: 2x43dBm CARRIERS
 VSWR: $\leq 1.1:1$ THRU 3GHz

NOTE: BOTH CONNECTORS WILL HAVE PROTECTIVE CAPS ON

4	CBL-SPO-250	1	1/4" SUPER FLEXIBLE	---
3	THT-64-427-3	1	CUSTOM LABEL	---
2	ST-P0375A-K	2	TUBING	HEAT SHRINK
1	RFN-1002-HPL	2	N PLUG CONNECTOR	WHITE BRONZE
#	PART NUMBER	QTY	DESCRIPTION	FINISH

CUSTOMER OUTLINE DRAWING	
ALL DIMENSIONS ARE REFERENCE ONLY	
UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES AND [MILLIMETERS]	
DRAWN C. ZUNIGA	05/20/20
CHECKED	
ORJ DRAWN C. ZUNIGA	05/20/20

RoHS COMPLIANT	
PROPRIETARY AND CONFIDENTIAL	
THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO RF INDUSTRIES. ANY UNAUTHORIZED USE OF THIS DRAWING IS EXPRESSLY PROHIBITED WITHOUT WRITTEN PERMISSION FROM RF INDUSTRIES. ANY VIOLATION IS PUNISHABLE UNDER U.S. COPYRIGHT LAWS.	

RFconnectors	
DIVISION OF RF INDUSTRIES, LTD.	
7610 MIRAMAR RD. SAN DIEGO, CA 92126 (858) 549-6340 (858) 549-6345 FAX	

N PLUG TO N PLUG			
SP0-250 CABLE ASSEMBLY			
SIZE A	CABLE GROUP HPL	DWG NO. P2RFC-2312-XX	REVISION —
SCALE: NTS	ENGINEERING ID: 000000	SHEET 1 OF 1	